

No	Model Name	(1)	(2)	(3)							(4)	(5)	(6)						(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)
		Rated heat output	Seasonal efficiency	Declared capacity for heating/Average climate							Bivalent temperature	Degradation coefficient	Declared coefficient of performance for heating/Average Climate						For air-to-water heat pumps: Operation limit temperature TOL	Heating water operating limit temperature WTOL	Electric power input				Capacity control	Sound power level	Rated air flow
		Prated	ηs	Pdh							Tbiv	Cdh	COPd								off mode	standby mode	thermostat-off mode	crankcase heater mode			
				Tj=-7°C	Tj=2°C	Tj=7°C	Tj=12°C	Tj=biv	Tj=OL	Tj=-15			Tj=-7°C	Tj=2°C	Tj=7°C	Tj=12°C	Tj=biv	Tj=OL									
kW	%	kW	kW	kW	kW	kW	kW	kW	°C								°C	°C	kW	kW	kW	kW	dB(A)	m³/h			
45	RUAGP511HL8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
46	RUAGP511HLN8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
47	RUAGP511HLR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
48	RUAGP511HLNR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
49	RUAGP511H18TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
50	RUAGP511H1N8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
51	RUAGP511H28TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
52	RUAGP511H2NR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
53	RUAGP511H2R8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
54	RUAGP511H2NR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
55	RUAGP511H38TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
56	RUAGP511H3NR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
57	RUAGP511H3R8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
58	RUAGP511H3NR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
59	RUAGP511H58TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
60	RUAGP511H5NR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
61	RUAGP511H5R8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
62	RUAGP511H5NR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
63	RUAGP511H78TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
64	RUAGP511H7NR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
65	RUAGP511H7R8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
66	RUAGP511H7NR8TR	180	171	122	74.5	48.3	20.7	138	138	-	-10	0.9	3.30	4.41	4.88	5.47	2.99	2.99	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
67	RUAGP511FL8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
68	RUAGP511FLN8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
69	RUAGP511FLR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
70	RUAGP511FLNR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
71	RUAGP511F18TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
72	RUAGP511F1N8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
73	RUAGP511F28TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
74	RUAGP511F2NR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
75	RUAGP511F2R8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
76	RUAGP511F2NR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
77	RUAGP511F38TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
78	RUAGP511F3NR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
79	RUAGP511F3R8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
80	RUAGP511F3NR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
81	RUAGP511F58TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
82	RUAGP511F5NR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
83	RUAGP511F5R8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
84	RUAGP511F5NR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
85	RUAGP511F78TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
86	RUAGP511F7NR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
87	RUAGP511F7R8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800
88	RUAGP511F7NR8TR	200	166	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.15	4.24	4.84	5.49	2.80	2.80	-10	55	0.239	-	1.832	0.239	variable	87.4	73,800