

No	Model Name	(1)	(2)	(3)							(4)	(5)	(6)						(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)
		Rated heat output	Seasonal efficiency	Declared capacity for heating/Average climate							Bivalent temperature	Degradation coefficient	Declared coefficient of performance for heating/Average Climate						For air-to-water heat pumps: Operation limit temperature TOL	Heating water operating limit temperature WTOL	Electric power input				Capacity control	Sound power level	Rated air flow
		Prated	ηs	Pdh							Tbiv	Cdh	COPd						TOL	WTOL	off mode	standby mode	thermostat-off mode	crankcase heater mode		Lwa	m³/h
				Tj=-7°C	Tj=2°C	Tj=7°C	Tj=12°C	Tj=biv	Tj=OL	Tj=-15			Tj=-7°C	Tj=2°C	Tj=7°C	Tj=12°C	Tj=biv	Tj=OL			Poff	Psb	Pto	Pck			
kW	%	kW	kW	kW	kW	kW	kW	kW	°C								°C	°C	kW	kW	kW	kW		dBA			
89	RUAGP561HL8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
90	RUAGP561HLN8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
91	RUAGP561HLR8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
92	RUAGP561HLNR8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
93	RUAGP561H28E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
94	RUAGP561H2N8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
95	RUAGP561H38E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
96	RUAGP561H3N8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
97	RUAGP561H3R8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
98	RUAGP561H3NR8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
99	RUAGP561H58E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
100	RUAGP561H5N8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
101	RUAGP561H5R8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
102	RUAGP561H5NR8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
103	RUAGP561H78E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
104	RUAGP561H7N8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
105	RUAGP561H7R8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800
106	RUAGP561H7NR8E	200	168	154	94.5	61.2	26.3	175	175	-	-10	0.9	3.18	4.33	4.84	5.49	2.82	2.82	-10	55	0.239	-	1.832	0.239	variable	90.9	73,800